

# DIRECTIONAL DRILLING SERVICES

## Float Subs With Float Valves Brochures

### Float SUB with Float VALVE

Model	OD in	ID in	Non-Valve fix end (pin/box)	The end fixed the valve (box)	Length in	Max. Work Pressure Psi
FF/2A30 x 2A10 x 950-0	3.5	1.5	NC26	2 3/8 Reg	37.44	5076 - 10153
FF/330 x 310 x 950-0	4.78	1.85	NC38	3 1/2 Reg	37.44	5076 - 10153
FF/330 x 310-0	4.78	1.85	NC38	4 1/2 Reg	36	5076 - 10153
FF/330 x 330-0	4.78	1.85	3 1/2 Reg	3 1/2 Reg	36	5076 - 10153
FF/330 x NC35B x 915-0	4.78	1.77	NC35B	2 1/2 Reg	36	5076 - 10153
FF/410 x 4A10-0	6.28	2.8	NC46	NC50	36	5076 - 10153
FF/430 x 310 x 950-0	6.48	2.65	NC38	4 1/2 Reg	37.44	5076 - 10153
FF/430 x 410 x 915-0	6.28	2.56	NC50	4 1/2 Reg	36	5076 - 10153
FF/430 x 410 x 915-0	6.75	2.8	NC50	4 1/2 Reg	36	5076 - 10153
FF/430 x 430 x 915-0	7.7	2.95	4 1/2 Reg	4 1/2 Reg	36	5076 - 10153
FF/430 x 4A10-0	6.28	2.56	NC46	4 1/2 Reg	36	5076 - 10153
FF/630 x 310 x 950-0	8	2.8	NC38	6 5/8 Reg	37.44	5076 - 10153
FF/630 x 630 x 915-0	8	2.8	6 5/8 Reg	6 5/8 Reg	36	5076 - 10153
FF/630 x 630-0	8.3	2.8	6 5/8 Reg	6 5/8 Reg	36	5076 - 10153
FF/730 x 630 x 915-0	9.03	3	6 5/8 Reg	7 5/8 Reg	36	5076 - 10153
FF/730 x 630-0	8.45	3	6 5/8 Reg	7 5/8 Reg	36	5076 - 10153
FF/730 x 730-0	8.45	3	7 5/8 Reg	7 5/8 Reg	36	5076 - 10153